



Engine hours: **Engine id:**

YAMAHA MAINTENANCE CHART

[illegible]

Item	Remarks	Initial	Every				Ref. page Service manual	OK ✓
		20h	100h Every 1 year	300h 3 year	500h 5 year	1000h		
LOWER UNIT								
Gear oil	Replace SAE 90/API GL-4 Amount:760 cm³ Counter rotation:715 cm³	•	•				10-14	
Pilot water / water inlet	Check	•	•				10-5	
Impeller (*1)	Check		•				8-8	
Impeller/Water pump	Replace			•			8-8	
Propeller / propeller shaft	Check / replace / grease	•	•				10-16	
GENERAL								
Battery	Check / replace / charge	•	•				10-4	
Anodes External	Check / replace		•				8-4 9-38	
Anodes Cylinder head / exhaust passage	Check / replace		•				7-57 7-74	
Anodes cylinder head, cylinder block thermostat portion, oil cooler cover and exhaust guide	Replace				•		7-74 7-81 9-30	
Wiring harness connections and coupler connections	Check / replace	•	•					
Engine start switch, main switch, engine start / stop button, engine shut-off switch	Check / replace	•	•				10-5	
Bolts and nuts, also for steering (*3)	Check / tighten	•	•					
Greasing points	Grease	•	•				10-15	
NOTES: (*1) Replace Impeller every 300h / 3 year (*2) Replace timing belt after 1.000h / 5 year (*3) Not cylinder head and crank case bolts (*4) Check / replace after 1.000h IMPORTANT! Ref: service manual 6EK-28197-ZT-11 Always check service manual and TSI for information!		----- DEALERS STAMP AND SIGNATURE						