



YAMAHA

Revs Your Heart

Owner:

Engine hours:

Engine id:

YAMAHA MAINTENANCE CHART

F75D F80D F80LB F90C F100F F100LB

Item	Actions	Initial	Every					OK ✓
		20h (3 months)	100h (Every 1 year)	300h (Every 3 year)	500h (Every 5 year)	1000h		
Anodes (External)	Inspection or replacement as necessary		•					
Anodes (Internal) *1	Inspection or replacement as necessary		•					
Anodes (Internal) *2	Replacement				•			
Battery (electrolyte level, terminal)	Inspection / fill or charge as necessary	•	•					
Cooling water leakage	Inspection or replacement as necessary	•	•					
Cowling lock lever	Inspection		•					
Engine starting and idle condition/ noise	Inspection	•	•					
Engine oil	Replacement	•	•					
Engine oil filter	Replacement		•					
Fuel filter	Inspection or replacement as necessary	•	•					
Fuel line (High pressure)	Inspection or replacement as necessary	•	•					
Fuel line (Low pressure)	Inspection or replacement as necessary	•	•					
Fuel pump	Inspection or replacement as necessary			•				
Fuel/ engine oil leakage	Inspection	•	•					
Gear oil	Replacement	•	•					
Greasing points	Greasing	•	•					
Clamp bracket bolt (through tube)	Inspection and greasing		•					
Impeller/ water pump housing	Inspection or replacement as necessary		•					
Impeller/ water pump housing	Replacement			•				

Power trim and tilt unit	Inspection	•	•				
Propeller/ propeller nut / cotter pin	Inspection or replacement as necessary	•	•				
PCV (pressure control valve)	Inspection or replacement as necessary		•				
Shift link/ shift cable	Inspection, adjustment or replacement as necessary	•	•				
Spark plugs	Inspection or replacement as necessary		•				
Spark plug caps/ wires	Inspection or replacement as necessary	•	•				
Shift Dampener System (SDS) propeller damper	Inspection or replacement as necessary		•				
Water from the cooling water pilot hole	Inspection	•	•				
Throttle link/ throttle cable	Inspection, adjustment or replacement as necessary	•	•				
Thermostat	Inspection or replacement as necessary		•				
Timing belt	Inspection or replacement as necessary		•				
Timing belt	Replacement					•	
Valve clearance	Inspection and adjustment					•	
Cooling water inlet	Inspection	•	•				
Main switch/ stop switch	Inspection or replacement as necessary	•	•				
Wire harness connections/ wire coupler connections	Inspection or replacement as necessary	•	•				
Yamaha meter/ gauge	Inspection	•	•				
Fuel tank (Yamaha portable tank)	Inspection and cleaning as necessary		•				
Exhaust guide/ exhaust manifold	Inspection or replacement as necessary					•	
NOTES: (*1) Cylinder head, cylinder block (*2) Cylinder head, cylinder block, fuel cooler, exhaust guide IMPORTANT! Ref: service manual 6FP-28197-HW-11 Always check service manual and TSI for information!		DEALERS STAMP AND SIGNATURE					